

### **MULTIDECK COOLERS**

Multideck coolers are one of the most popular refrigerated merchandisers for coffee shops, supermarkets, hotels, schools, universities, delicatessens, restaurants and hospitals. With the increase in 'grab & go' service, our Multideck coolers have never been in such demand!





Their designer style improves your front of house, while their clever layout maximizes every millimeter of retail space. MGPRO's Multideck range are perfect for front of house display, enhancing presentation and giving customers open, easy access to drinks, prepacked snacks and dairy products.





# KEY FEATURES

#### **ENERGY SAVING**

Setting new standards: To help reduce energy consumption we've introduced LED lighting as standard across the entire showcases and multideck coolers range. As well as cutting power consumption, they make the display look even more attractive and if you want the ultimate in energy efficiency, our optional front opening doors deliver substantial energy savings.

#### OPERATING TEMPERATURE

The ideal operating temperature in all multideck coolers is +4 to +6 degrees celcius at an ambient temperature of 26 degrees celcius.

#### MOBILITY

All multideck coolers and showcases are built with swivel and brake (no mark leaving) castors. This makes it easier for moving them around or to clean the area below the multideck cooler.

#### ADJUSTABLE SHELVES

All multideck coolers come with two glass shelves plus the bottom. The glass shelves are easily adjustable in height as per the requirement / application.

#### OPTIONAL / EXTRA

- •Extra glass shelf is available.
- •Extra lighting.
- •Roll-down night blind.
- Opening glass doors.
- Front digital temperature display







# TECHNICAL DATA

| Outer Dimensions  | 48 x 27.56 x 51.57 inch             |
|---|-------------------------------------|
| Temperature Range   | +4 to +8 degrees C                  |
| Ambient temperature   | 26 degrees C                        |
| No. of Shelves  | Two toughened black glass shelves   |
| Specification of SS used for Inner Tank / Outer Body                  | SS 304                              |
| Specification of Glass  | Toughened glass                     |
| Specification of Light  | Water proof strip LED               |
| Condensing Unit   | No frost cooling                    |
| Refrigerant   | R 134a                              |
| Material for structural work & body                                   | SS 202                              |
| Frost free refrigeration system with soft cold airflow with blow fans | Yes                                 |
| Electronic digital temperature controller with automatic defrost      | Yes                                 |
| Fibber Castors wheels   | Two with brakes & two without brake |





















## **Contact Information**

#### Corporate Office:

Hospitality Appliances Pvt. Ltd. Ground floor, Hema House, Chandawarkar road, Opposite Dattani trade centre, Borivali West, Mumbai 400091, Maharashtra, India.

Email: sales@hapl.co.in / mukeshganjawalla@yahoo.com

Tel. +91 22 28959893 / 9894 Website: www.hapl.co.in

#### Factory / Works:

Ganjawalla FabriPro Pvt. Ltd.

Plot No. 47, Government Industrial estate (Phase 2), Piparia, Silvassa, UT of Dadra & Nagar Haveli, India

Email: <u>gfpl.silvassa@gmail.com</u> Tel. +91 260 2640989 / 2641989

Allow adequate space for maintenance and ventilation. All refrigeration equipment requires adequate ventilation for efficient and effective performance. MGPRO reserves the right to modify the design, materials and finish in accordance with its progressive development policy.

